

MATERIAL SAFETY DATA SHEET

1 OF 2

Section I: IDENTIFICATION

Product Name: Acrylic Mounting Medium

Date Prepared: 06/02

Item Number(s): 3349-04, 3349-16

Emergency Phone: 800-424-9300

Section II: HAZARDOUS INGREDIENTS

<i>Hazardous Component(s):</i>	<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>	<i>NFPA</i>
<i>Toluene ~60%</i>	<i>108-88-3</i>	<i>200 50/150 ppm</i>	<i>Health 2 Flammability 3</i>
<i>Resin ~40%</i>		<i>NA</i>	<i>Reactivity 0</i>

Section III: PHYSICAL DATA

<i>Boiling Point: 232°F</i>	<i>Specific Gravity (H₂O = 1): >1</i>
<i>Vapor Pressure mm Hg/20°C: 38</i>	<i>Percent Volatile by Vol: 100%</i>
<i>Vapor Density (Air 1:1): 4.5</i>	<i>Evaporation Rate (ether = 1): 4.5</i>
<i>Solubility in H₂O: No</i>	<i>Appearance & Odor: Light yellow liquid, characteristic odor</i>

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: 40°F TCC *Flammable Limits: LEL 1.2 UEL 7.0*

Extinguishing Media: Water spray, dry chemical, CO₂ and foam for alcohol

Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.

Unusual Fire & Explosion Hazards: Eliminate sources of ignition. Burns with invisible flame.

Section V: REACTIVITY

Stability: Stable *Material to Avoid: Strong oxidizers*

Hazardous Decomposition or Byproducts: Oxides of carbon

Hazardous Polymerization: Does not occur *Conditions to Avoid: Excessive heat, sparks or flames*

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion

Acute: Vapors may cause eyes, skin and respiratory irritation, drowsiness, nausea, headache and vomiting.

Chronic: May cause liver, heart, kidney damage, gastrointestinal disturbances and convulsions.

Carcinogenicity: Not classified as a human carcinogen.

Signs/Symptoms of Exposure: Vision blurring, eye irritation, drowsiness and headache.

MATERIAL SAFETY DATA SHEET

MM T, 2 OF 2

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persist.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Eliminate source of ignition in the vicinity of the spill or released vapor. Isolate the spill area with sand, or other absorbent material. Place all contaminated material in closed container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use precautions for flammable liquids. Avoid excessive heat and sources of ignition. For large quantities, store in flammable safety cabinet. Use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Special flammable exhaust hood if vapor concentration is high. In well-ventilated areas, mechanical exhaust is sufficient.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.
