

MATERIAL SAFETY DATA SHEET-#SP900-25

1 OF 10

Section I: IDENTIFICATION

Product Name: **Neat Stain Trichrome**
Trichrome, Chamber #4

Date Prepared: 04/24/03
Item Number(s): SP 900-25
Emergency Phone: 800-424-9300

Section II: COMPOSITION

<i>Component(s):</i>	<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>	<i>NFPA</i>	
Acetic Acid < 1%	64-19-7	NA	Health	1
Phosphotungstic < 1%	12501-23-4	NA	Flammability	0
Chromotrope 2R < 1%	4197-07-3	NA	Reactivity	0

Section III: PHYSICAL DATA

<i>Boiling Point:</i>	~212°F	<i>Specific Gravity (H₂O = 1):</i>	1
<i>Vapor Pressure mm Hg/20°C:</i>	1	<i>Percent Volatile by Vol:</i>	NR
<i>Vapor Density (Air 1:1):</i>	2	<i>Evaporation Rate (ether = 1):</i>	<1
<i>Solubility in H₂O:</i>	Complete	<i>Appearance & Odor:</i>	Purple liquid/slight vinegar odor

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: Not Flammable

Extinguishing Media: Water spray, dry chemical, CO₂ and foam

Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.

Unusual Fire & Explosion Hazards: None Known

Section V: REACTIVITY

Stability: Stable *Material to Avoid:* Strong oxidizers, chromic anhydride, perchloric acids etc.

Hazardous Decomposition or Byproducts: Oxides of carbon, nitrogen and chlorine

Hazardous Polymerization: Does not occur *Conditions to Avoid:* Excessive heat

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion *Target Organs:* Nervous system, liver and eyes

Acute: Vapors may cause eyes, skin and respiratory irritation.

Chronic: May cause liver damage and gastrointestinal disturbances.

Carcinogenicity: Not classified as a human carcinogen.

Signs/Symptoms of Exposure: Skin and respiratory irritation.

MATERIAL SAFETY DATA SHEET

SP900-25 Chromo 2 OF 10

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persists.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Isolate the spill area with sand, or other absorbent material. Place all contaminated material in close container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use normal precautions. Avoid excessive heat. For large quantities, use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Normal mechanical exhaust hood or ventilated areas.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.

MATERIAL SAFETY DATA SHEET

Section I: IDENTIFICATION

Product Name: **Trichrome**

Iodine Alcohol, Chamber #1

Date Prepared: 04/24/03

Item Number(s): SP 900-25 et al

Emergency Phone: 800-424-9300

Section II: COMPOSITION

<i>Component(s):</i>		<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>		<i>NFPA</i>	
Methanol	< 4%	67-56-1	200	200/250	Health	1
Ethanol	<67%	64-17-5	1000	1000/NA	Flammability	3
PVP Iodine	< 1%	7553-56-2	NA		Reactivity	0

Section III: PHYSICAL DATA

Boiling Point: 80°F

Vapor Pressure mm Hg/20°C: 40

Vapor Density (Air 1:1): 1.6

Solubility in H₂O: Complete

Specific Gravity (H₂O = 1): 0.9

Percent Volatile by Vol: 91%

Evaporation Rate (ether = 1): >1

Appearance & Odor: Red/maroon liquid/alcohol odor

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: 55°F TCC

Flammable Limits: LEL 3.3

UEL 19

Extinguishing Media: Water spray, dry chemical, CO₂ and foam for alcohol

Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.

Unusual Fire & Explosion Hazards: Eliminate sources of ignition. Burns with invisible flame.

Section V: REACTIVITY

Stability: Stable *Material to Avoid:* Strong oxidizers, chromic anhydride, perchloric acids etc.

Hazardous Decomposition or Byproducts: Oxides of carbon and nitrogen

Hazardous Polymerization: Does not occur *Conditions to Avoid:* Excessive heat, sparks or flames

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion *Target Organs:* Kidneys, nervous system, liver and eyes

Acute: Vapors may cause eyes, skin and respiratory irritation, drowsiness, nausea, headache and vomiting.

Chronic: May cause liver, heart, kidney damage, gastrointestinal disturbances and convulsions.

Carcinogenicity: Not classified as a human carcinogen.

Signs/Symptoms of Exposure: Vision blurring, drowsiness and headache.

MATERIAL SAFETY DATA SHEET

SP900-25 I/A 4 OF 10

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persists.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Eliminate source of ignition in the vicinity of the spill or released vapor. Isolate the spill area with sand, or other absorbent material. Place all contaminated material in close container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use precautions for flammable liquids. Avoid excessive heat and sources of ignition. For large quantities, store in flammable safety cabinet. Use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Special flammable exhaust hood if vapor concentration is high. In well-ventilated areas, mechanical exhaust is sufficient.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.

MATERIAL SAFETY DATA SHEET

5 OF 10

Section I: IDENTIFICATION

Product Name: **Neat Stain Trichrome**
Acid Alcohol, Chamber #5

Date Prepared: 04/24/03
Item Number(s): SP 900-25
Emergency Phone: 800-424-9300

Section II: COMPOSITION

<i>Component(s):</i>	<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>		<i>NFPA</i>	
Methanol < 5%	67-56-1	200	200/250	Health	1
Ethanol <90%	64-17-5	1000	1000/NA	Flammability	3
Acetic Acid < 1%	64-19-7	NA		Reactivity	0

Section III: PHYSICAL DATA

Boiling Point: 80°F
Vapor Pressure mm Hg/20°C: 40
Vapor Density (Air 1:1): 1.6
Solubility in H₂O: Complete

Specific Gravity (H₂O = 1): 0.8
Percent Volatile by Vol: 91%
Evaporation Rate (ether = 1): >1
Appearance & Odor: Clear liquid/alcohol odor

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: 55°F TCC
Flammable Limits: LEL 3.3 UEL 19
Extinguishing Media: Water spray, dry chemical, CO₂ and foam for alcohol
Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.
Unusual Fire & Explosion Hazards: Eliminate sources of ignition. Burns with invisible flame.

Section V: REACTIVITY

Stability: Stable
Material to Avoid: Strong oxidizers, chromic anhydride, perchloric acids etc.
Hazardous Decomposition or Byproducts: Oxides of carbon and nitrogen
Hazardous Polymerization: Does not occur
Conditions to Avoid: Excessive heat, sparks or flames

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion
Target Organs: Kidneys, nervous system, liver and eyes
Acute: Vapors may cause eyes, skin and respiratory irritation, drowsiness, nausea, headache and vomiting.
Chronic: May cause liver, heart, kidney damage, gastrointestinal disturbances and convulsions.
Carcinogenicity: Not classified as a human carcinogen.
Signs/Symptoms of Exposure: Vision blurring, drowsiness and headache.

MATERIAL SAFETY DATA SHEET

SP900-25 AA 6 OF 10

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persists.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Eliminate source of ignition in the vicinity of the spill or released vapor. Isolate the spill area with sand, or other absorbent material. Place all contaminated material in close container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use precautions for flammable liquids. Avoid excessive heat and sources of ignition. For large quantities, store in flammable safety cabinet. Use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Special flammable exhaust hood if vapor concentration is high. In well-ventilated areas, mechanical exhaust is sufficient.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.

MATERIAL SAFETY DATA SHEET

Section I: IDENTIFICATION

Product Name: **Neat Stain Trichrome**

Alcohol 95%, Chamber #6 & 7

Date Prepared: 04/24/03

Item Number(s): SP 900-25

Emergency Phone: 800-424-9300

Section II: COMPOSITION

<i>Component(s):</i>	<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>		<i>NFPA</i>	
Methanol < 5%	67-56-1	200	200/250	Health	1
Ethanol <90%	64-17-5	1000	1000/NA	Flammability	3
				Reactivity	0

Section III: PHYSICAL DATA

Boiling Point: 80°F

Vapor Pressure mm Hg/20°C: 40

Vapor Density (Air 1:1): 1.6

Solubility in H₂O: Complete

Specific Gravity (H₂O = 1): 0.8

Percent Volatile by Vol: 91%

Evaporation Rate (ether = 1): >1

Appearance & Odor: Clear liquid/alcohol odor

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: 55°F TCC

Flammable Limits: LEL 3.3

UEL 19

Extinguishing Media: Water spray, dry chemical, CO₂ and foam for alcohol

Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.

Unusual Fire & Explosion Hazards: Eliminate sources of ignition. Burns with invisible flame.

Section V: REACTIVITY

Stability: Stable *Material to Avoid:* Strong oxidizers, chromic anhydride, perchloric acids etc.

Hazardous Decomposition or Byproducts: Oxides of carbon and nitrogen

Hazardous Polymerization: Does not occur *Conditions to Avoid:* Excessive heat, sparks or flames

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion *Target Organs:* Kidneys, nervous system, liver and eyes

Acute: Vapors may cause eyes, skin and respiratory irritation, drowsiness, nausea, headache and vomiting.

Chronic: May cause liver, heart, kidney damage, gastrointestinal disturbances and convulsions.

Carcinogenicity: Not classified as a human carcinogen.

Signs/Symptoms of Exposure: Vision blurring, drowsiness and headache.

MATERIAL SAFETY DATA SHEET

SP900-25 A 95% 8 OF 10

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persists.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Eliminate source of ignition in the vicinity of the spill or released vapor. Isolate the spill area with sand, or other absorbent material. Place all contaminated material in close container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use precautions for flammable liquids. Avoid excessive heat and sources of ignition. For large quantities, store in flammable safety cabinet. Use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Special flammable exhaust hood if vapor concentration is high. In well-ventilated areas, mechanical exhaust is sufficient.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.

MATERIAL SAFETY DATA SHEET

Section I: IDENTIFICATION

Product Name: **Neat Stain Trichrome**
70% Alcohol, Chamber #2 & 3

Date Prepared: 04/24/03
Item Number(s): SP 900-25
Emergency Phone: 800-424-9300

Section II: COMPOSITION

<i>Component(s):</i>	<i>CAS Number</i>	<i>OHSA PEL, ACGIH TLV/STEL</i>		<i>NFPA</i>	
Methanol < 4%	67-56-1	200	200/250	Health	1
Ethanol <67%	64-17-5	1000	1000/NA	Flammability	3
				Reactivity	0

Section III: PHYSICAL DATA

Boiling Point: 80°F
Vapor Pressure mm Hg/20°C: 40
Vapor Density (Air 1:1): 1.6
Solubility in H₂O: Complete

Specific Gravity (H₂O = 1): 0.9
Percent Volatile by Vol: 91%
Evaporation Rate (ether = 1): >1
Appearance & Odor: Clear liquid/alcohol odor

Section IV: FIRE/EXPLOSION HAZARD

Flash Point: 55°F TCC
Flammable Limits: LEL 3.3 UEL 19

Extinguishing Media: Water spray, dry chemical, CO₂ and foam for alcohol

Special Fire Fighting Procedures: Wear protective clothing with NIOSH approved breathing apparatus. Products of combustion may be harmful in a fire situation. Do not use direct water stream.

Unusual Fire & Explosion Hazards: Eliminate sources of ignition. Burns with invisible flame.

Section V: REACTIVITY

Stability: Stable
Material to Avoid: Strong oxidizers, chromic anhydride, perchloric acids etc.

Hazardous Decomposition or Byproducts: Oxides of carbon and nitrogen

Hazardous Polymerization: Does not occur
Conditions to Avoid: Excessive heat, sparks or flames

Section VI: HEALTH HAZARDS

Routes of Entry: Inhalation, Skin and Ingestion
Target Organs: Kidneys, nervous system, liver and eyes

Acute: Vapors may cause eyes, skin and respiratory irritation, drowsiness, nausea, headache and vomiting.

Chronic: May cause liver, heart, kidney damage, gastrointestinal disturbances and convulsions.

Carcinogenicity: Not classified as a human carcinogen.

Signs/Symptoms of Exposure: Vision blurring, drowsiness and headache.

MATERIAL SAFETY DATA SHEET

SP900-25 70%A 10 OF 10

Section VI: HEALTH HAZARDS

Emergency First Aid:

Skin: Remove contaminated clothing. Wash affected area with soap and water.

Eyes: Thoroughly flush eyes with water. Contact a physician if irritation persists.

Ingestion: Rinse mouth thoroughly with water, provided person is conscious and contact a physician.

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration and contact physician.

Section VII: SAFE HANDLING

Chemical Release or Spill: Eliminate source of ignition in the vicinity of the spill or released vapor. Isolate the spill area with sand, or other absorbent material. Place all contaminated material in close container for disposal.

Waste Disposal Method: All liquid and or contaminated material should be disposed of in DOT approved waste containers. Incineration for liquids is the suggested method of disposal. Comply with all Federal, State and Local regulations for disposal.

Precautions for Handling and Storing: Use precautions for flammable liquids. Avoid excessive heat and sources of ignition. For large quantities, store in flammable safety cabinet. Use in well-ventilated area.

Section VIII: CONTROL MEASURES

Respiratory Protection: Not normally required. If used in a poorly ventilated area use under an approved fume hood or NIOSH approved respirator.

Ventilation: Special flammable exhaust hood if vapor concentration is high. In well-ventilated areas, mechanical exhaust is sufficient.

Protective Gloves: Chemical resistant *Eye Protection:* Safety glasses

Other Protective Clothing or Equipment: Normal laboratory apparel suggested by Good Laboratory Practices

Work/Hygienic Practices: Wash thoroughly with soap and water after handling.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Astraldiagnosics shall not be held liable for any damage resulting from handling or contact with this product.
