

Safety Data Sheet

Clearview

Revision Date: 02/05/19

1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|-------------------------------------|---|
| 1.1 Product identifier | Trade name: Clearview Product code(s): 7023-G |
| 1.2 Relevant identified uses | Laboratory Reagent |
| Supplier: | Astral Diagnostics Inc. 800-441-0366 Technical Service Monday-Friday: 8:00 -5:00 PM |
| Synonym: | None. |
| Material uses: | Laboratory Reagent. |
| Validation date: | 12/11/2013 |
| In case of emergency: | 800-424-9300 CHEMTREC (USA) 24 Hours/Day: 7 Days/Week |

2. HAZARDS IDENTIFICATION

Emergency Overview:

GHS Label Elements: Pictogram



Signal Word:

Danger!

Hazard statement(s):

H225: Highly flammable liquid and vapor

H303: May be harmful if swallowed

H315: Causes skin irritation

H319: Causes serious eye irritation

H370: Causes damage to organs

Precautionary statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P280: Wear protective gloves/ eye protection/ face protection.

P305+351+338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

NFPA Rating

Health hazard: 1

HMIS Classification

Health hazard: 1

Fire: 3
Reactivity Hazard: 0

Flammability: 3
Physical hazards: 0

Potential Health Effects : Inhalation – May cause respiratory tract irritation.
Skin - May cause skin irritation.
Eyes – May cause eye irritation.
Ingestion – Potentially toxic if swallowed in large quantities.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Name | CAS number | % by volume |
|------------------------|------------|-------------|
| Ethanol | 64-17-5 | <73 |
| Isopropanol | 64-17-5 | <4 |
| Acetic Acid | 108-10-1 | <10 |
| Methyl Isobutyl Ketone | 108-10-1 | <1 |
| Methanol | 67-56-1 | <4 |
| Water | 7732-18-5 | Balance |

4. FIRST AID MEASURES

First-aid measures general: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: *Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.*

First-aid measures after skin contact: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

First-aid measures after eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media: Do not use a heavy water stream

5.2 Special hazards arising from the substance or mixture

No additional information available

5.3 Advice for firefighters

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment: Gloves. Safety glasses. Combined gas/dust mask with filter type B/P3.
Emergency procedures: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment: Equip cleanup crew with proper protection.
Emergency procedures: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safe handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, vapors, spray. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood.

Hygiene measures: Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures: Comply with applicable regulations.

Storage conditions: Keep container closed when not in use. Protect from sunlight. Store in a well-ventilated place.

Incompatible products: Strong oxidizers. Strong reducing agents. Strong bases.

Incompatible materials: Sources of ignition. Direct sunlight

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult local authorities for acceptable exposure limits.

| Component | Source | Type | Value | Note |
|-------------------|--------|------------|---------------------------------|------|
| Ethanol | ACGIH | STEL | 1000 ppm 15 min | |
| | OSHA | PEL (TWA) | 1000 ppm 8 hrs | |
| | OSHA | TWA (ppm) | 1000 ppm 10 hrs | |
| Methyl Alcohol | ACGH | TWA | 200 ppm | |
| | ACGH | STEL | 250 ppm | |
| | NIOSH | TWA | 260 mg/m ³ , 200 ppm | |
| | OSHA | TWA | 260 mg/m ³ , 200 ppm | |
| Acetic Acid | ACGIH | TWA | 10 ppm | |
| | ACGIH | STEL | 15 ppm | |
| | OSHA | TWA | 25 mg/m ³ , 10 ppm | |
| | NIOSH | REL (TWA) | 25 mg/m ³ , 10 ppm | |
| | NIOSH | REL (STEL) | 37 mg/m ³ , 15ppm | |
| Isopropyl Alcohol | ACGIH | TWA | 200 ppm | |
| | OSHA | TWA | 400 ppm | |
| | ACGIH | STEL | 400 ppm | |

Personal protective equipment: Safety glasses. Gloves. Protective clothing. High gas/vapor concentration: gas mask with filter type B.

Hand protection: Wear protective gloves.

Eye protection: Chemical goggles or face shield.

Skin and body protection: Wear suitable protective clothing.

Respiratory protection: Wear appropriate mask. Gas mask with filter type B.

Other information: Do not eat, drink or smoke during use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Flash Point: Closed cup: 43°C

pH: NA

Melting/freezing point: NA

Vapor pressure: NA

Odor threshold: NA

VOC: NA

Color: Clear

Odor: Characteristic

Boiling/condensation point: NA

Relative density: NA

Vapor density: NA

Evaporation rate: NA

Solubility: Soluble in the following materials: water

10. STABILITY AND REACTIVITY

10.1. Reactivity

No further relevant information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

High temperatures, flames, sparks

10.5. Incompatible materials

Strong oxidizers. Strong acids.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide, nitrogen oxides, hydrogen chloride gas

11. TOXICOLOGICAL INFORMATION

Phloxine B (18472-87-2)

LD50 oral rat 8400 mg/kg

Water (7732-18-5)

LD50 oral rat ≥ 90000 mg/kg

ATE US (oral) 90000.000 mg/kg body weight

Methanol (67-56-1)

LD50 oral rat 1187-2769 mg/kg

LC50 inhalation rat (mg/l) 128.2 mg/l (4hr)

LC50 inhalation rat (mg/l) 87.6 mg/l (6hr)

LD50 Dermal rabbit 17100 mg/kg

Isopropyl Alcohol (67-63-0)

LD50 Dermal rabbit 12870 mg/kg

LC50 inhalation rat 73 mg/l/4h

ATE US (oral) 5045 mg/kg body weight

Skin corrosion/irritation: Not classified

Serious eye damage/irritation: Causes eye irritation

Respiratory or skin sensitization: Not classified

Germ cell mutagenicity: Not classified

Carcinogenicity: Not Classified

12. ECOLOGICAL INFORMATION

| | | | |
|--------------------------------------|--------------------|-----------------|-----------------|
| Toxicity | | | |
| | Ethanol | LC50 fish | 14200 mg/l |
| | Methanol | LC50 fish 1 | 15400 mg/l |
| | | EC50 Daphnia 1 | 18260 mg/l |
| | | ErC50 algae | 22000 mg/l |
| | Isopropanol | LC50 fish 2 | 9640 mg/l |
| | | EC Daphnia 2 | 13299 mg/l |
| Persistence and Degradability | Ethanol | BOD | 0.8-0.967 gO2/g |
| | | COD | 1.7 gO2/g |
| | | ThOD | 2.1 gO2/g |
| | Methanol | BOD | 0.6-1.12 gO2/g |
| | | COD | 1.42 gO2/g |
| | | ThOD | 2.1 gO2/g |
| | Isopropanol | BOD | 1.19 gO2/g |
| | | COD | 2.23 gO2/g |
| | | ThOD | 2.4 gO2/g |
| Bioaccumulative potential | Ethanol | BCF fish 1 | 1 |
| | | Log Pow | -0.31 |
| | Methanol | BCF fish 1 | 1-4.5 |
| | | Log Pow | -0.77 |
| | Isopropanol | Log Pow | 0.05 |
| Mobility | Ethanol | Surface Tension | 0.022 N/m |
| | Methanol | Surface Tension | 0.023 N/m |
| | | Log Koc | -0.89-0.21 |
| | Isopropanol | Surface Tension | 0.021 N/m |
| PBT and vPvB assessment | No data available | | |
| Other | No data available | | |

13. DISPOSAL CONSIDERATIONS

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

DOT

UN No. UN1987
Proper Shipping Name Alcohol NOS (ethanol/methanol/MIBK)
Hazard Class 3
Packing Group II

IATA

UN No. UN1987
Proper Shipping Name Alcohol NOS (ethanol/methanol/MIBK)
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

15. REGULATORY INFORMATION

15.1 US Federal Regulations

All components are listed on the United States TSCA (Toxic Substances Control Act) inventory
Methanol

RQ 5000lb

SARA Section 311-312 Hazard classes : Flammable, Acute toxicity

15.2 International Regulations

All components are listed on the Canadian DSL (Domestic Substances List)

15.3 US State regulations


California Proposition 65



WARNING: This product can expose you to chemicals including Methanol and Methyl Isobutyl Ketone, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

16. OTHER INFORMATION

National Fire Protection Association (U.S.A.)



Notice to reader

This Safety Data Sheet has been prepared in accordance with the Globally Harmonized System for the Classification and Labeling of Chemicals (GHS). To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries makes any warranty of merchantability or any other warranty, expressed or implied, which respect to such information, and we assume no liability resulting from its use. In no event shall Astral Diagnostics, Inc be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages resulting from use of or reliance upon this information.